



Fine Pitch Metric Hex Head Cap Screws
DIN 960 & DIN 961

Fully Threaded
8.8 Heat Treated Alloy Steel • Black Finish
Tensile Strength: 116,000 PSI

Part No.	Diameter & Pitch	Length	Unit Pkg.
8mm (13mm Hex)			
11255	8mm-1.00	10mm	10
11259	8mm-1.00	40mm	10
14604*	8mm-1.00	50mm	25
10mm (17mm Hex)			
11262	10mm-1.00	30mm	10
11263	10mm-1.00	40mm	10
14605	10mm-1.25	20mm	10
11265	10mm-1.25	25mm	10
11266	10mm-1.25	30mm	10
11267	10mm-1.25	35mm	10
11268	10mm-1.25	40mm	10
11269	10mm-1.25	50mm	10
14606*	10mm-1.25	60mm	10
12mm (19mm Hex)			
11270	12mm-1.25	25mm	10
14607	12mm-1.25	30mm	5
11271	12mm-1.25	35mm	5
14608	12mm-1.25	40mm	5
14610*	12mm-1.25	70mm	5
11273	12mm-1.50	20mm	10
11274	12mm-1.50	30mm	10
11275	12mm-1.50	40mm	5
11276	12mm-1.50	50mm	5
14mm (22mm Hex)			
14611	14mm-1.50	30mm	5
14612	14mm-1.50	40mm	5
14613	14mm-1.50	50mm	5
24048	14mm-2.00	80mm	5
16mm (24mm Hex)			
14617	16mm-1.50	40mm	5

*DIN 931 - Not Fully Threaded



Metric Hex Socket Head Cap Screw
DIN 912

Regular Pitch - Grade 12.9
Heat Treated Alloy Steel • Plain Finish
Tensile Strength: 177,000 PSI

Part No.	Unit Package	Diameter & Pitch	Length
10845	100	4mm-.7	12mm
10846		5mm-.8	12mm
10848	10875	5mm-.8	20mm
10851		6mm-1.00	16mm
10854		6mm-1.00	30mm
10855		8mm-1.25	16mm
10858		8mm-1.25	30mm
10861		10mm-1.50	20mm
10864		10mm-1.50	40mm
10865		10mm-1.50	50mm
10866		12mm-1.75	30mm
10868		12mm-1.75	40mm
10870		12mm-1.75	60mm



Metric Flat Head Socket Cap Screws
DIN 7991

Regular Pitch - Grade 10.9
Heat Treated Alloy Steel • Plain Finish
Tensile Strength 150,800 PSI

Part No.	Unit Package	Diameter & Pitch	Length
10960	100	6mm-1.00	16mm
10972		8mm-1.25	25mm



Metric Hex Key
Plain Finish

Use with Din 912 & Din 7991

Part No.	Hex Size	For Screw Size	Unit Pkg.
7965	3mm	4mm	10